

AMP-204C / AMP-208C

DSP-based 4/8-axis Advanced Pulse-Train Motion Controllers



Features

- Onboard floating-point DSP
- 4/8 axis pulse-train command up to 6.5MHz
- Trajectory cycle time up to 1 KHz
- Encoder feedback frequency up to 20 MHz with digital filter design
- High speed position latch function via ORG and Index signals
- High speed position comparison and trigger output up to 1MHz for auto-optical inspection
- 32 additional onboard digital I/O channels (16DI & 16DO) save the cost of a full DI/O card
- PWM control of laser application
- Programmable interrupt source control to host PC
- Watchdog timer for safety control
- Includes ADLINK's MotionCreatorPro 2™ suite of graphical installation, 3D trajectory plot, and data sampling for diagnostic programs
- Support for up to 16 cards in a single system

Motion Features

- Jogging mode
- Pre-defined engineering unit
- Any 2-6 axis linear interpolation
- Any 3 axis circular interpolation
- Any 3 axis spiral interpolation (incl. helical interpolation)
- Multi-axis synchronous motion (Master-Slave)
 - Gantry mode
 - Electronic gear
- Point table function for contouring application
- Velocity planning and point-table functions support contouring applications
- Safety level setting prevents damage to mechanism and operator
- Trapezoidal, S-curve velocity, user-defined profile
- Position override & speed override anytime
- Variety of homing modes via ORG and index signals
- Backlash compensation

Software Support

- OS Information
 - Windows® 8/7/XP
- Software Compatibility
 - VB/VB++/BCB/VB.NET
 - Various sample programs with source code
- Software Recommendations
 - MotionCreatorPro2

Specifications

Motion Control

■ Positioning Range	4×10^{15} counts
■ Speed Programming Range	32,767,000 count / sec
■ Max. Acceleration Rate	4×10^{15} counts / sec ²

Pulse Output Channels

■ Number of Channels	4-CH for AMP-204C; 8-CH for AMP-208C
■ Pulse Output Rate	6.55 Mpps (max.)
■ Pulse Output Mode	CW/CCW, OUT/DIR

Encoder Input Channels

■ Number of Channels	4-CH for AMP-204C; 8-CH for AMP-208C
■ Max. Encoder Input Frequency	20 MHz under 4xAB mode
■ Encoder Input Modes	OUT/DIR, CW/CCW and 1x/2x/4x AB phase

Trigger Channels

■ Number of Trigger Output Channels	2-CH for AMP-204C; 4-CH for AMP-208C
■ Position Compared Method	Linear / FIFO
■ FIFO Size	16 per channel (hardware-based) ; 5,000 per channel (software-based)
■ Trigger Pulse Output Frequency	1 MHz for linear comparison ; 1 MHz for FIFO comparison (hardware-based) 500 Hz for FIFO comparison (software-based)
■ Trigger Pulse Width	0.2 μ s to 167 ms

Motion I/O Interface Signals

■ I/O Pin	2500 V _{RMS} optically isolated on DIN-825-GP4
■ Encoder Index Signal Input	EZ
■ Mechanical Limit Switch Signal Input Pin	\pm EL and ORG
■ Servomotor Interface I/O Pin	INP, ALM, SVON
■ Miscellaneous Pin	IEMG, TRG (PWM)

General Purpose Isolated I/O (on DIN-825-GP4 Series)

■ Digital Input	20-CH (for AMP-204C) and 24-CH (for AMP-208C) digital input
■ Input Voltage	0 to 24 V
■ Input Resistance	4.7 k Ω @ 0.5 W
■ Digital Output	20-CH (for AMP-204C) and 24-CH (for AMP-208C) digital output
■ Output Voltage	5 V (Min.) ; 35 V (Max.)
■ Output Type	NPN open collector
■ Sink Current	90 mA

General Specifications

■ Connectors	100-pin SCSI-VHDCI type connector
■ Operating Temperature	0°C to +55°C (32°F to 131°F)
■ Storage Temperature	+20°C to +80°C (68°F to 176°F)
■ Humidity	5% to 95%, non-condensing

Pin Assignment

AMP-204C & AMP-208C

DGND	1	51	IEMG
Rsv.	2	52	Rsv.
Rsv.	3	53	Rsv.
Rsv.	4	54	Rsv.
Rsv.	5	55	Rsv.
Rsv.	6	56	Rsv.
Rsv.	7	57	Rsv.
Rsv.	8	58	Rsv.
Rsv.	9	59	Rsv.
Rsv.	10	60	Rsv.
EA5V	11	61	DGND
EA5V	12	62	DGND
OUT1+	13	63	OUT3+
OUT1-	14	64	OUT3-
DIR1+	15	65	DIR3+
DIR1-	16	66	DIR3-
OUT2+	17	67	OUT4+
OUT2-	18	68	OUT4-
DIR2+	19	69	DIR4+
DIR2-	20	70	DIR4-
TRG1+	21	71	TRG2+
TRG1-	22	72	TRG2-
EA1+	23	73	EA3+
EA1-	24	74	EA3-
EB1+	25	75	EB3+
EB1-	26	76	EB3-
EZ1+	27	77	EZ3+
EZ1-	28	78	EZ3-
EA2+	29	79	EA4+
EA2-	30	80	EA4-
EB2+	31	81	EB4+
EB2-	32	82	EB4-
EZ2+	33	83	EZ4+
EZ2-	34	84	EZ4-
ALM1	35	85	ALM3
ORG1	36	86	ORG3
SVON1	37	87	SVON3
PEL1	38	88	PEL3
INP1	39	89	INP3
MEL1	40	90	MEL3
ALM2	41	91	ALM4
ORG2	42	92	ORG4
SVON2	43	93	SVON4
PEL2	44	94	PEL4
INP2	45	95	INP4
MEL2	46	96	MEL4
EDO1	47	97	EDO3
ED1	48	98	ED13
EDO2	49	99	EDO4
ED12	50	100	ED14

Ordering Information

■ AMP-204C

DSP-based 4-axis advanced pulse-train motion controller

■ AMP-208C

DSP-based 8-axis advanced pulse-train motion controller

Accessories

For more information on terminal boards & cables, please refer to page 3-30.

Terminal Board

■ DIN-825-GP4

Terminal board with 100-pin SCSI-II connector for general purpose servo & stepper

Cable

■ ACL-102100-1

100-pin SCSI-II cable, 1M

■ SCSI-VHDCI 100P

100-pin SCSI VHDCI cable, available for 2 M, 3 M and 5 M