



### Features

- Sustained read up to 420 MB/s
- Sustained write up to 380 MB/s
- Capacity: 32, 64, 128 GB
- SATA 6 Gb/s interface
- Single-Level Cell NAND Flash for longer life
- Industrial Temperatures: -40°C~85°C
- Shock and vibration resistant

### Specifications

#### Physical

Capacity	32, 64, 128 GB
Flash Components	Single-Level Cell (SLC) NAND
Interface	SATA 6 Gb/s
Form Factor	2.5" form factor
Dimensions	100 x 68.85 x 9.5mm (L x W x H)
Weight	80 g

#### Performance

Bandwidth	32 GB: Sustained read/write up to 360/170 MB/s
	64 GB: Sustained read/write up to 400/275 MB/s
	128 GB: Sustained read/write up to 420/380 MB/s
Read and Write IOPS	32 GB: Random 4KB read/write up to 17,000/8,500 IOPS
	64 GB: Random 4KB read/write up to 17,500/11,000 IOPS
	128 GB: Random 4KB read/write up to 17,000/10,000 IOPS
Power On to Ready	<1.0 sec

#### Environmental

Operating Temperature	Commercial: 0°C to 70°C
	Industrial: -40°C to 85°C
Storage Temperature	-40°C to 85°C
Shock	1,500 G, 0.5 ms
Vibration	Operating: 7~800Hz, 2.17 Grms
	Non-operating: 7~800Hz, 3.08 Grms
Certifications	UL, CE, RoHS, Microsoft WHQL

#### Compatibility

SATA	SATA Revision 3.0 compliant: compatible with SATA 1.5 Gb/s, 3 Gb/s & 6 Gb/s interface
	ATA/ATAPI- 8 compliant
	SSD enhanced SMART ATA feature set
	Native Command Queuing (NCQ) command set
	TRIM supported

#### Power Requirements

Management	5V SATA SATA interface power management OS-aware hot plug/removal
Connector	15-pin SATA connector for DC 5V input

#### Reliability

MTBF	> 2,000,000 hours
Life Cycle	Minimum of 5 years useful life

### Ordering Information

Model Number	Description/Configuration
<b>ASD25-SLC32G-ET</b>	2.5" SATA 6 Gb/s SSD 32 GB, SLC type, (-40°C~85°C)
<b>ASD25-SLC64G-ET</b>	2.5" SATA 6 Gb/s SSD 64 GB, SLC type, (-40°C~85°C)
<b>ASD25-SLC128G-ET</b>	2.5" SATA 6 Gb/s SSD 128 GB, SLC type, (-40°C~85°C)
<b>ASD25-SLC32G-CT</b>	2.5" SATA 6 Gb/s SSD 32 GB, SLC type, (0°C~70°C)
<b>ASD25-SLC64G-CT</b>	2.5" SATA 6 Gb/s SSD 64 GB, SLC type, (0°C~70°C)
<b>ASD25-SLC128G-CT</b>	2.5" SATA 6 Gb/s SSD 128 GB, SLC type, (0°C~70°C)

### Dimensions

