

# RK-622

## 6U Rackmount Industrial Chassis with 20-slot Backplane ❖



### Features

- EIA RS-310C 19" rackmount Standard 6U chassis
- Fault detection/alarm notification
- Hot-swap redundant power supply
- Hot-swap four 9 cm filter cooling fans
- USB connector and PS/2 keyboard connector ready inside front door
- Four 5.25" shock-resistant drive bays
- Support various backplane and power supply unit

### Ordering Information

Model Name	Color	Backplane	Power Supply
NS-622-19S18A-400	Beige	HPCI-19S18A	APS-6400P

#### Power Supply Options

Model Number	Watt	Input Range	Output (Max.)					Current Type	
			+5 V	+3.3 V	+12 V	-12 V	-5 V		+5 Vsb
APS-6460P	460 W	95-264 full Range	35 A	28 A	20 A	1 A	0.8 A	2 A	EPS12
APS-946XA-EPS12	460 W	95-264 full Range	40 A	30 A	32 A	1 A	0.8 A	2 A	EPS12

### Specifications

Dimensions	19 x 10.5 x 18.4 inch (480 x 266 x 467 mm) (W x H x D)
Drive Bays	Four 5.25" front accessible drive bays
Construction	Heavy-Duty Steel
Color Options	Beige: standard Others: call for availability
Cooling Fans	In: four 92 x 92 x 25 mm ball bearing fans
Front Panel	Front door with lock System reset switch , ATX Power switch and alarm reset switch PS/2 keyboard connector and USB connector
Rear Panel Option	Supports 20-slot passive backplane Supports PS2 form factor ATX Redundant ATX power supply unit
Carton Size	24.8 x 17.3 x 24 inch (630 x 440 x 610 mm)
Weight	17 kg/37.4 lbs

#### Backplane Options

Model Name	PICMG® CPU	PCI™	ISA	PSU Connector
HPCI-19S18A	2	18	--	ATX / AT

### Dimensions

Units: mm

