

MilSystem™ 840

Extreme Rugged™ Intel® Core™2 Duo
COTS Military Computer



Features

- Passive convection-cooled chassis
- Intel® Core™2 Duo system
- Tested to MIL-STD-810F standards
- Uniquely-keyed D38999 connectors
- Internal expansion for Mini PCI and PCIe Mini Card
- Wide range input: 12 to 32 VDC
- Windows® XP Professional or Ubuntu Linux® pre-installed
- Windows® CE, QNX®, and VxWorks® supported



Featuring: COM 840 with Intel® Core™2 Duo 1.6GHz and 965GME Chipset

Designed with Ampro by ADLINK™ Extreme Rugged™ COM 840 and EBX baseboard

- Size (WxHxD): 8x10x3"
- IP50 rated chassis

Specifications

Board Compatibility

COM 840 with rugged EBX Carrier Board

High performance, conduction cooled 1.6GHz Intel® Core™2 Duo L7500 processor
Chipset – Intel® GME965/ICH8

Modular/Expandable

Mini PCI and PCI Express Mini Card

I/O

SATA – 1x Internal HDD or SSD (up to 128GB)
– 1x External

CompactFlash

VGA – supporting up to 2048 x 1536 resolution

Ethernet – 2x GbE

Serial – 4 ports, 2 supporting RS-232/422/485

Parallel – EPP/ECP bidirectional port

Floppy – Supported by USB (bootable)

USB – 4 USB 2.0 ports (4 root hubs)

PS/2 – Keyboard

Audio – Speaker-out, Line-in, Mic

LVDS

Remote ATX power and indicators

Network Interface

Ethernet – Dual, Intel® 82541 (Gigabit) and Intel® 82551ER (10/100BaseT)

Operating Systems

Available with Windows® XP Professional or Ubuntu Linux® pre-installed
Support for Windows® CE, QNX® or VxWorks®

Mechanical

Size (WxHxD): 8x10x3"

Environmental

Temperature

- Standard: –20°C to +65°C
- Extended: –40°C to +75°C
- Storage: –40°C to +85°C

IP50 rated

Complies with MIL-STD-810G military standards for shock and vibration

Power

- 14–32 VDC (standard)
- 12–25 VDC (optional)

Ordering Information

Model Number	Description/Configuration
MIL840W-02010-1101	MilSystem™ 840, 1.6GHz Core 2 Duo L7500, 32GB SSD, 2GB RAM, WinXP Professional, 14-32VDC, RoHS
MIL840W-02010-A101	MilSystem™ 840, 1.6GHz Core 2 Duo L7500, 32GB SSD, 2GB RAM, Ubuntu 8.04 LTS, 14-32VDC, RoHS
MIL840W-03030-1101	MilSystem™ 840, 1.6GHz Core 2 Duo L7500, 128GB SSD, 4GB RAM, WinXP Professional, 14-32VDC, RoHS
MIL840W-03030-A101	MilSystem™ 840, 1.6GHz Core 2 Duo L7500, 128GB SSD, 4GB RAM, Ubuntu 8.04 LTS, 14-32VDC, RoHS
MIL-ACC-US	MilSystem™ Starter Kit: MC1, MC2, MC3 breakout cables, AC adapter, software, and documentation

Other configurations available. Please contact your salesperson.