

DIN-Rail Power Supplies

: DIN-Rail 24/48 VDC Power Supplies

	DR-4524	DR-75-24	DR-120-24	DR-75-48	DR-120-48
DIN-Rail 24/48 VDC Power Supplies					
Dimensions Unit: mm (inch) (W x H x D)	 78 x 67 x 93 mm	 55.5 x 100 x 125.2 mm	 65.5 x 100 x 125.2 mm	 55.5 x 100 x 125.2 mm	 65.5 x 100 x 125.2 mm
Power	45W	75W	120W	75W	120W
Input	85-264 VAC (47-63 Hz) or 120-370 VDC		88-132 VAC/ 176-264 VAC (47-63 Hz) by switch or 248-370 VDC	85-264 VAC (47-63 Hz) or 120-370 VDC	88-132 VAC/ 176-264 VAC (47-63 Hz) by switch or 248-370 VDC
Output	48W, 24 VDC, 0-2A	76.8W, 24 VDC, 0-3.2A	120W, 24 VDC, 0-5A	76.8W, 48 VDC, 0-1.6A	120W, 48 VDC, 0-2.5A
Over Voltage protection	115-135% of rated output voltage	29-33V			
Overload Protection	105-150%				
Type	Constant Current Limiting				
Reset	Auto Recovery				
Inrush current	30A/115V or 60A/230V				
Weight	400 g	550 g	650 g	550 g	650 g
Working Temp. and Relative Humidity	-10 to 50°C to 90% RH	-10 to 60°C, 20 to 90% RH			
Warranty	3 years				
Safety Standards	TÜV EN60950-1, UL508 Approved				
EMC Standards	CISPR22 (EN55022) class B, EN61000-4-2, 3, 4, 5, 6, 8, 11, ENV50204, EN61000-3-2, -3, EN50082-2				

: Ordering Information

- DR-4524:** 45W/2A DIN-Rail 24 VDC Power Supply with universal 85 to 264 VAC input
- DR-75-24:** 75W/3.2A DIN-Rail 24 VDC Power Supply with universal 85 to 264 VAC input
- DR-120-24:** 120W/5A DIN-Rail 24 VDC Power Supply with 88 to 132 VAC/176 to 264 VAC input by switch
- DR-75-48:** 75W/1.6A DIN-Rail 48 VDC Power Supply with universal 85 to 264 VAC input
- DR-120-48:** 120W/2.5A DIN-Rail 48 VDC Power Supply with 88 to 132 VAC/176 to 264 VAC input by switch